



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : A61M 25/16, 25/18, 39/00, 39/10</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/67833 (43) International Publication Date: 16 November 2000 (16.11.00)</p>
<p>(21) International Application Number: PCT/US00/12621 (22) International Filing Date: 9 May 2000 (09.05.00) (30) Priority Data: 09/309,652 10 May 1999 (10.05.99) US (71) Applicant: ADVANCED UROSCIENCE, INC. [US/US]; 1290 Hammond Road, St. Paul, MN 55110 (US). (72) Inventors: KLEIN, Dean, A.; 27 Raven Road, North Oaks, MN 55127 (US). BRAZIL, James, D.; 1174 413th Avenue N.W., Braham, MN 55006 (US). WHITE, Daniel, A.; 2004 Runnymede Court, Minnetonka, MN 55305 (US). (74) Agents: NAWROCKI, Lawrence, M. et al.; Nawrocki, Rooney & Sivertson, P.A., Suite 401, 3433 Broadway Street N.E., Minneapolis, MN 55413 (US).</p>		<p>(81) Designated States: CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i></p>
<p>(54) Title: IMPROVED LUER FITTING INJECTOR</p> <div data-bbox="298 1182 1175 1520"> </div> <p>(57) Abstract</p> <p>This invention is an improved Luer lock fitting for hypodermic needles, and methods for using the fitting to inject suspended solids into a body. The improved fitting includes a lumen (36) having a curvedly tapered, distally decreasing throat region, which is believed to provide improved flow of suspended solids into the hypodermic needles. One fitting includes at least two threads (50) to provide a more secure fitting able to withstand higher injection pressures. Another fitting includes rounded wings (54) better able to withstand jarring by endoscope eyepieces, and resisting being dislodged from position. One method includes injecting suspended solids into soft tissue such as sphincter mechanisms. One method includes injecting suspended solids into tissue surrounding a mechanism to correct defects.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

IMPROVED LUER FITTING INJECTOR

Field of the Invention

The present application is related to devices and methods for injecting suspended solids into a body. Specifically, the present invention is related to a hypodermic needle assembly and hub having a curvedly tapered lumen and higher pressure Luer-lock fittings for joining syringes to hypodermic needles, and methods for using same.

10 Background of the Invention

Hypodermic needles are commonly used to inject fluids into a body. It will be understood that injection of fluids occurs both with respect to human bodies and animal bodies. While the present invention, in its preferred embodiment, is intended for use in injecting fluids into a human body, veterinary applications are specifically contemplated. The needles have a sharpened distal end and often have a hub fitting on the proximal end for mating to a syringe. The fitting is often a Luer fitting, which describes generally the male-female shapes of the syringe and needle hub, respectively. When the Luer fitting includes means such as threads for locking the male and female parts together, the fitting is known as a Luer-lock tip. The Luer-lock fitting is a standard fitting in the medical field, often having a single

thread having nominally three turns about the longitudinal axis of the syringe. The Luer-lock fitting is well suited for administering agents such as drugs through common hypodermic needle lengths.

5 A composition and method for treating urinary incontinence is described in related U.S. Patent Application Serial No. 08/676,592, filed July 8, 1996, entitled IMPROVED TISSUE INJECTABLE COMPOSITION AND METHOD OF USE, herein incorporated by reference. The composition includes solid
10 particles having an average size of between about 100 and 1,000 microns, preferably between 200 and 500 microns. The particles can be carried in a suspension such as a fluid or gel.

Standard Luer-lock fittings have been used to inject the
15 particles into a body through the employment of endoscopes, but with less than optimal results due in part to problems related to the particular application. One problem is the long needle lengths required for the application. Needle lengths are dictated both by anatomy and by the length of
20 endoscopes used in the procedures. Needles used in injecting solids into the urinary sphincter muscles are nominally 16 inches long. Needles used in injecting solids into esophageal sphincter can be about 60 inches long. The longer internal

paths have a higher resistance to flow than the shorter paths typically found in hypodermic needles.

Another problem is related to the nature of the injected composition. The injectable material includes solid particles
5 suspended in a carrier, such as a gel. A typical Luer-lock fitting includes a lumen having a large inside diameter proximal end and a smaller inside diameter distal end. The transition from large inside diameter to small inside diameter can be a step change or a straight taper, as the shapes are
10 easy to mold and manufacture. These transition taper shapes work well with typical liquids, but work less than optimally with large particles suspended in a liquid carrier. In particular, the particles can be swept along a straight taper region to a location immediately proximal of the small inside
15 diameter portion, and become bunched up at this point. The particles massed at one point can prevent the further passage of any particles. What would be desirable is a Luer-lock fitting better able to lessen the blockage by the large particles.

20 Still another problem with conventional Luer-lock fittings is the use of a single thread. Attempting to force large, possibly bunched, suspended particles suspended in a viscous carrier through long hypodermic needles can require

high pressure. In practice, this can require a great deal of hand pressure on the plunger of a syringe. In practice, this high pressure can result in fluid leakage at the Luer-lock fitting. The loss of the fluid can be a significant problem, as it serves as the carrier for the particles. With loss of the carrier in the Luer-lock fitting, the particles become more concentrated, and less likely for flow through the fitting and into the hypodermic needle lumen. What would be desirable is a fitting better able to withstand the high pressures required to inject suspended solids through hypodermic needles.

Summary of the Invention

The present invention includes a hypodermic needle having an improved Luer-lock fitting for injection of suspended solids through the needle. The present invention includes methods for using the improved fitting to inject solid particles suspended in a viscous carrier through long hypotube sections and into soft tissue to treat deficiencies. Applicants believe the present invention reduces the blockage of Luer fittings by large, suspended solid particles. Applicants also believe the present invention provides a fitting better able to withstand the higher pressures applied

when injecting viscous suspensions through long hypotube sections.

One improved fitting according to the present invention includes a substantially cylindrical or tubular hub body affixed to the proximal end of a hypodermic needle. The hub body has a proximal end for receiving fluid, a distal end for ejecting fluid, a lumen therethrough, and a hub body wall having a threaded region. The body includes a region having a curvedly tapered inside diameter, decreasing the inside diameter with increasing distal position. The curved taper region is preferably disposed distally of a standard, straight, Luer tapered region. The curved taper is believed to reduce the likelihood of blockage from particles bunching up near the taper distal end. Blockages have been observed in Luer fittings having straight tapers. Such blockages can preclude further particle flow and can cause large back pressures. Applicants believe even small blockages can preferentially allow flow of a suspension fluid over flow of suspended particles, concentrating the particles in less fluid until the blockage becomes more pronounced.

A preferred embodiment has more than a single thread, providing a tighter, pressure resistant seal between syringe and Luer-lock fitting. One fitting has two start threads 180

degrees opposed, each wrapping around the fitting for about 1 and $\frac{1}{2}$ turns. One fitting hub has two opposed wings extending outward from the longitudinal axis of the hub. The wings provide a structure for tightly grasping and turning the hub
5 relative to the syringe. Preferred wings have a rounded periphery. The rounded wings can deflect objects striking the wings, lessening the force which can act to dislodge a positioned hypodermic needle. In particular, the rounded wings can deflect an endoscope eyepiece knocking against the
10 hub.

In use, a long hypodermic needle having a Luer-lock hub according to the present invention is provided. A suspension of solids in a liquid carrier is provided in a syringe adapted to mate to the Luer-lock fitting. The syringe is secured to
15 the Luer-lock fitting at a point in time as dictated by the user. In one method, the syringe is secured before advancing the needle into the patient. In another method, the syringe is secured only after the needle tip has been advanced close to the target site. The needle is preferably advanced through
20 an endoscope such that the sharp needle tip is visualized as the tip is advanced.

The sharp needle tip can be advanced until the target site is penetrated, and the syringe plunger depressed until a

sufficient amount of solid suspension has been injected into the target. The needle can be retracted and advanced to different target sites until the area has been treated. A preferred use of the present invention is the augmentation of urinary, anal and gastric sphincter mechanisms with injected solid particles.

Brief Description of the Drawings

FIG. 1 is a perspective view of a system for injecting suspended solids, including a syringe and hypodermic needle with hub having a Luer-lock fitting and rounded wings;

FIG. 2 is a top view of a the hypodermic needle and hub of FIG. 1; and

FIG. 3 is a longitudinal cross-sectional view of the Luer-lock hub fitting of FIG. 1 (with wings not shown), illustrating the curvedly tapered lumen region.

Detailed Description of the Preferred Embodiments

FIG. 1 illustrates a system 20 for injecting suspended solids including a syringe 22 and a hypodermic needle assembly 24. Syringe 20 includes a generally cylindrical body 28 having a distal portion 30 and a threaded region 32. Disposed within syringe body 28 is a plunger 26 having a distal portion 40 and rubber seals 38. Syringe 22 has a tapered, protruding

male member 34 having a lumen 36 therethrough. Member 34, in a preferred embodiment, has a standard Luer taper.

Hypodermic assembly 24 includes a proximal hub 42 and a needle 44. Needle 44 is commonly formed of hypotube and is illustrated having a protective sheath 46 disposed over needle 44. Hub 42 includes a threaded cylindrical region 50 having a lumen 48 therethrough. Lumen 48 substantially defines the longitudinal axis of hypodermic needle assembly 24. Threaded cylindrical region 50 includes an inner wall surface 52, preferably having a standard Luer taper adapted to mate with syringe member 34. In hub threaded region 50, a preferred embodiment has more than one start thread, to provide additional sealing force over the length of threaded regions 50 and 32 when tightened. In the embodiment of FIG.1, hub threaded region 50 has two start threads, with one start indicated at 54 and the other disposed 180 degrees opposite. In this embodiment, each of the two threads wraps 1 and $\frac{1}{2}$ turns about the hub. Some previous devices have utilized only a single thread which has sometimes proven less than optimal in retaining the suspension carrier fluid within the Luer-lock fitting under pressure. Other previous hub devices have utilized only protruding, stub-like ears in place of threads. These devices have sometimes proven unable to provide

sufficient strength when a user attempted to provide a tight seal between syringe and hub. Hub 42 includes two wings 54, each having a thinner, internal portion 56, and a thicker, rounded, peripheral rib portion 58.

5 Referring now to FIG. 2, hypodermic needle assembly 24 is further illustrated in greater detail. In a preferred embodiment, hub lumen 48 includes a Luer taper region 62 and a curvedly tapered region 60. Curvedly tapered region 60 is indicated by phantom lines in FIG. 2, illustrating the lumen
10 through hub 42, which continues through needle 44. Needle 44 terminates in a distal skived portion 64. In a preferred embodiment, wings 54 are consistently oriented relative to skived portion 64. In one embodiment, wings 54 are oriented such that the widest portions of skived portion 64, as
15 indicated at 65, are oriented outward in the same direction as wings 54. This orientation of skived portion 64 provides a predictable configuration that is consistent with the insertion of the needle tip through an endoscope while lessening the chance of wings 54 being dislodged by the
20 endoscope eyepiece.

A preferred embodiment hub has wings to aid in securing a tight, pressure resistant fitting for the Luer-lock fitting. At least some prior art devices for injecting suspended solids

have lacked wings. These device hubs have proven difficult to grasp tightly and held with latex gloved hands. The prior device drawbacks have sometimes lead users to affix clamps to the hypodermic hub in order to rotate the hub and syringe
5 sufficiently tightly so as to form a tight seal. Wings 54 have a rounded periphery in a preferred embodiment, as illustrated in FIG. 2. The rounded periphery provides a rounded surface such that if another device, such as an endoscope eye-piece, collides with the wings, the other device
10 can glance off the wings rather than connect squarely and risk dislodging a previously positioned needle tip.

Referring now to FIG. 3, Luer taper 62 and curved taper 60 are illustrated in detail. In one embodiment, Luer taper 62 is a straight, ANSI taper, tapering from 0.170 inch inside
15 diameter to 0.155 inch inside diameter over a length of 0.250 inch. In one embodiment, curved taper 60 extends from a proximal bend point 70 to a distal bend point 72, having curved portion 60 therebetween. The curvedly tapered region in one embodiment is substantially non-linearly distally
20 decreasing. In one embodiment, curved portion 60 has a shape described by a parabola. In another embodiment, curved portion 60 has a shape described by a logarithmic function. In a preferred embodiment, the surface of curve 60 changes

less per unit distance with increasing distal position, having a steeper slope near proximal bend point 70. Applicants believe curved taper 60 provides an orderly transition for the suspended beads or particles being forced into the hypodermic
5 needle. Applicants believe the curved transition region substantially lessens the occurrence of particles jamming together and blocking or substantially increasing the back pressure in lumen 48. Applicants have experienced blockage when attempting to inject a solid suspension through a fitting
10 having a straight taper rather than a curved taper. The particles were observed to bunch together near the taper distal end, preventing further passage of particles and creating large back-pressure in the lumen, in response to continued applied syringe plunger pressure.

15 In use, the user can select an appropriate needle length to use and an appropriate solid suspension. After inserting and positioning an endoscope, the targeted site can be visualized and identified. A preferred use of the present invention is augmenting soft tissue with injected solid
20 particles. While a preferred method utilizes an endoscope, other visualization methods such as fluoroscopy are also within the scope of the invention. Syringe 22 can be filled with an appropriate amount of solid suspension. Hypodermic

needle assembly 24 can be filled with the solid suspension or other inert fluid and inserted into the endoscope. In a preferred method, hub wings 54 are properly oriented so as to properly orient needle skived portion 64 so as to optimally
5 pierce the targeted site, such as a sphincter mechanism.

Syringe 22 can be secured to hypodermic needle assembly 24 by inserting syringe 22 into hub lumen 48 and rotating syringe 22 relative to hub 42 while holding hub wings 54 firmly. In one method, syringe and hub are secured together
10 after the needle has been inserted into the endoscope. In another method, syringe and hub are secured together prior to inserting the hypodermic needle into the endoscope. Using the endoscope, needle distal skived portion 64 can be incrementally moved into position and into the targeted site
15 in a sphincter mechanism. The rounded hub wings of the preferred embodiment should provide resistance to the needle being dislodged, should the wings be jarred during advancement through the endoscope, such as during an inadvertent collision with the endoscope eyepiece.

20 Once in place, suspended solids can be injected into the target site. The wings and multiple threads of the preferred embodiment provide structure to enable the formation of a tight, pressure resistant seal between syringe and needle hub.

The curved taper of the present invention provides resistance to blockage which can be caused by the accumulation of the particles to be injected. The needle can be repeatedly retracted and advanced into multiple tissue sites proximate a location until treatment is complete. The needle and endoscope can then be withdrawn.

Numerous characteristics and advantages of the invention covered by this document have been set forth in the foregoing description. It will be understood, however, that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of parts without exceeding the scope of the invention. The inventions's scope is, of course, defined in the language in which the appended claims are expressed.

15

What is claimed is:

1. An improved Luer-lock fitting comprising:
a tubular body including a longitudinal axis and a tubular body wall, a lumen therethrough, a proximal end for receiving fluid, and a distal end for ejecting fluid, said proximal end tubular body wall having a threaded region, said lumen having a curvedly tapered inside diameter region.
2. An improved Luer-lock fitting as recited in Claim 1 wherein said curved taper is distally decreasing.
3. An improved Luer-lock fitting as recited in Claim 2 wherein said curved taper is substantially continuously non-linearly distally decreasing.
4. An improved Luer-lock fitting as recited in Claim 2 wherein said threaded region has more than one thread.
5. An improved Luer-lock fitting as recited in Claim 4 wherein said threaded region has two threads.

6. An improved Luer-lock fitting as recited in Claim 5 wherein each of said two threads complete more than a single turn about said longitudinal axis.

7. An improved Luer-lock fitting as recited in Claim 4 further comprising two wings extending outwardly from said longitudinal axis, said wings having a rounded periphery.

8. A method for injecting suspensions of solids in liquids into a body comprising:

providing a needle having a longitudinal axis including

a distal end for ejecting fluid, a proximal end for receiving fluid, and a lumen therethrough, and

a Luer-lock fitting disposed on said needle proximal end having a generally cylindrical body, a distal end, a proximal end, a lumen therethrough, and a cylinder wall, said proximal end cylinder wall having a threaded region therein, said lumen having a curvedly tapered inside diameter;

providing a syringe having a plunger and threads adapted to mate to said Luer-lock fitting;

providing a suspension of solids within said syringe;

attaching said syringe to said Luer-lock fitting;
positioning said needle distal end into a target body location; and
injecting said suspension from said syringe through said curved taper, through said needle lumen, and into said body target.

9. A method as recited in Claim 8 wherein said solids have an average diameter of at least about 80 microns.

10. A method as recited in Claim 8 wherein said Luer-lock fitting threaded region includes at least two threads, such that a higher pressure connection relative to a single thread fitting between said Luer-lock fitting and said syringe can be formed.

11. A method as recited in Claim 10 wherein
said Luer-lock fitting includes at least two wings extending outwardly from said longitudinal axis, said wings having a rounded periphery, such that an object striking said rounded wings has a tendency to glance off said wings, and

said attaching step includes holding said wings while rotating said syringe and Luer-lock fitting relative to one another.

12. A system for injecting a solid suspension comprising:

a needle having a longitudinal axis including a distal end for ejecting fluid, a proximal end for receiving fluid, and a lumen therethrough;

a Luer-lock fitting disposed on said needle proximal end having a generally cylindrical body, a distal end, a proximal end, a lumen therethrough, and a cylinder wall, said proximal end cylinder wall having a threaded region therein, said lumen having a curvedly tapered inside diameter; and

a syringe having a plunger and threads adapted to mate to said Luer-lock fitting.

13. A system for injecting a solid suspension as recited in Claim 12 wherein said Luer-lock fitting threaded region is internal to said cylinder wall.

14. A system for injecting a solid suspension as recited in Claim 13 wherein said Luer-lock fitting threaded region includes at least two threads.

15. A system for injecting a solid suspension as recited in Claim 13 wherein said Luer-lock fitting includes at least two rounded wings extending outwardly from said longitudinal axis.

16. An hypodermic needle assembly for injecting suspended solids into a body comprising:




a hypodermic needle having a lumen therethrough, a distal end, and a proximal end; and

a tubular hub disposed near said needle proximal end including a longitudinal axis and a tubular hub wall, a lumen therethrough, a proximal end for receiving fluid, and a distal end for ejecting fluid, said proximal end tubular hub wall having a threaded region, said hub having means for reducing plugging by said solids.

17. A hypodermic needle assembly as recited in Claim 16 wherein said hub includes means for firmly grasping and rotating said hub with a human hand.

18. A hypodermic needle assembly as recited in Claim 17 wherein said hub includes means for forming a tight, pressure resistant seal with a syringe.

19. A hypodermic needle assembly as recited in Claim 17 wherein said means for grasping includes means for deflecting objects striking said means for grasping.

Fig. 1*Fig. 2**Fig. 3*

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/12621

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A61M 25/16, 25/18, 39/60, 39/10

US CL : 604/533

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 604/167.04, 256, 533

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

BRS

Search Terms: Luer, lock, thread, wing, taper

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,441,487 A (VEDDER) 15 August 1995, entire patent.	1-19
Y	US 5,785,693 A (HAINING) 28 July 1998, entire patent.	1-19
A, E	US 6,063,062 A (PARADIS) 16 May 2000, entire patent.	1-19
A	US 5,743,883 A (VISCONTI) 28 April 1998, entire patent.	1-19

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*I* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

16 JUNE 2000

Date of mailing of the international search report

30 AUG 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MICHAEL M THOMPSON

Telephone No. (703) 305-1619